

(12) UK Patent Application (19) GB (11) 2 355 538 (13) A

(43) Date of Printing by UK Office 25.04.2001

(21) Application No 0100784.8
(22) Date of Filing 17.06.1999
(30) Priority Data
(31) 19982827 (32) 18.06.1998 (33) NO
(86) International Application Data
PCT/NO99/00199 En 17.06.1999
(87) International Publication Data
WO00/00850 En 06.01.2000

(51) INT CL⁷
G01V 3/30
(52) UK CL (Edition S)
G1N NCLE N19B2A
(56) Documents Cited by ISA
WO 98/12417 A1 US 5303773 A US 5233304 A
(58) Field of Search by ISA
INT CL⁶ G01V


(71) Applicant(s)
Den Norske Stats Oljeselskap a.s.
(Incorporated in Norway)
N-4035 Stavanger, Norway

(72) Inventor(s)
Fan-Nian Kong
Harald Westerdahl
Terje Eidesmo
Svein Ellingsrud

(74) Agent and/or Address for Service
Kilburn & Strode
20 Red Lion Street, LONDON, WC1R 4PJ,
United Kingdom

(54) Abstract Title
Device and method for measurement of resistivity outside of a wellpipe

(57) The invention is a device for measuring and surveillance of resistivity in a petroleum reservoir in a geological formation with an injection-, observation- or production well comprising an electrically conductive metallic well tubing, with the new and inventive being characterized by the following features: a) an electrical energy source; b) at least one inductive transmitter antenna for electromagnetic waves, fixedly arranged in the well, outside of the well tubing's outer metallic surface; c) at least one series of sensors comprising n inductive resistivity sensors (5a, 5b, ..., 5n) arranged for receiving the electromagnetic waves and generation of measurement signals, fixedly arranged in the well, by the petroleum reservoir and outside the well tubing's outer metallic surface; and d) a signal conductor for the measurements signals.



GB 2 355 538 A